

High Torque BELLEVILLE WASHER ----HIGH TEMPERATURE -200 ~300 °C

Recommended Material 17-4PH, 17-7PH, 15-7PH

Precipitation hardening stainless steel

Corrosion resistance and high temperature

| Art No. | Bolt Size | Dimensions (mm) | | | | Recommended torque P/N*m |
|---------|-----------|-----------------|-------|-------|-------|-----------------------------|
| | | D | d | t | Ho | |
| 570001 | M8 | 15.00 | 8.40 | 1.50 | 1.70 | 22 |
| 570002 | M10 | 19.00 | 10.50 | 2.00 | 2.25 | 35 |
| 570003 | M12 | 22.00 | 12.50 | 2.50 | 2.75 | 50 |
| 570004 | M14 | 26.00 | 14.50 | 2.50 | 2.80 | 70 |
| 570005 | M16 | 30.00 | 16.80 | 3.00 | 3.40 | 110 |
| 570006 | M18 | 34.00 | 18.80 | 3.50 | 3.45 | 140 |
| 570007 | M20 | 38.00 | 20.80 | 4.00 | 4.45 | 220 |
| 570008 | M22 | 42.00 | 22.80 | 4.00 | 4.55 | 300 |
| 570009 | M24 | 46.00 | 24.80 | 4.50 | 5.10 | 390 |
| 570010 | M27 | 52.00 | 27.80 | 4.50 | 5.20 | 550 |
| 570011 | M30 | 56.00 | 30.80 | 5.00 | 5.75 | 650 |
| 570012 | M32 | 60.00 | 32.80 | 5.00 | 5.85 | 750 |
| 570013 | M36 | 68.00 | 36.80 | 6.00 | 6.90 | 960 |
| 570014 | M38 | 72.00 | 38.80 | 6.00 | 7.30 | 1550 |
| 570015 | M39 | 76.00 | 39.80 | 6.00 | 7.40 | 2260 |
| 570016 | M42 | 80.00 | 43.00 | 7.00 | 7.70 | 3120 |
| 570017 | M46 | 86.00 | 46.80 | 8.00 | 8.30 | 4270 |
| 570018 | M48 | 92.00 | 49.00 | 8.00 | 9.50 | 5970 |
| 570019 | M52 | 98.00 | 53.00 | 8.00 | 9.80 | 6900 |
| 570020 | M56 | 112.00 | 57.00 | 8.00 | 9.80 | 7600 |
| 570021 | M60 | 115.00 | 61.50 | 8.00 | 9.80 | 8300 |
| 570022 | M64 | 120.00 | 65.50 | 9.00 | 11.00 | 9350 |
| 570023 | M72 | 128.00 | 73.50 | 11.00 | 13.00 | 9350 |
| 570024 | M82 | 156.00 | 83.50 | 13.00 | 15.50 | 10020 |