



Per Viti for Thread	Specification mm					Test load daN	h after test	N.W. 1K (pcs) kg
	D	d	e	h				
M6	17	6.5	2.4	0.80		320	0.60	3.60
M8	20	8.5	2.8	0.95		400	0.70	5.60
M10	23	10.5	3.2	1.05		600	0.80	7.90
M12	26	12.5	4.0	1.30		1150	1.00	13.00
M14	29	15.5	4.8	1.30		1300	0.90	18.00
M16	33	17.0	4.8	1.40		1250	1.10	24.00
M18	37	19.0	6.0	1.52		2100	1.20	35.00
M20	41	21.0	6.0	1.85		2100	1.40	45.00
M22	45	23.0	7.2	1.67		2700	1.40	60.00
M24	50	25.0	7.2	1.84		2900	1.60	81.00
M27	56	28.5	8.0	1.80		3600	1.60	115.00
M30	60	32.0	8.8	2.30		4200	1.80	170.00
M33	64	35.0	10.0	2.57		6300	2.00	190.00
M36	68	38.0	10.0	2.50		6200	2.00	210.00
M39	72	41.0	10.0	2.45		5500	2.20	223.00
M42	76	44.0	10.0	3.20		5700	2.40	240.00
M45	80	47.0	10.0	2.75		6500	2.50	280.00
M48	85	50.0	10.0	2.85		5700	2.60	370.00
M52	90	54.0	12.0	3.55		7500	2.80	405.00
M56	95	58.0	12.0	3.22		7200	3.00	441.00
M60	100	62.0	12.0	3.25		7000	3.00	